



DOHERTY
COUPLERS AND ATTACHMENTS
A KINSHOFER COMPANY

BTA SERIES OF

Rotary Tilt Buckets



WWW.DOHERTYDIRECT.NET

Rotary Tilt Bucket



Maximum 'Uptime' - Minimum Maintenance Costs

The BTA series of Rotary Tilt Buckets are the ultimate shaping tool and are used by operators who understand the value of maximum "uptime" and minimal maintenance costs.

BTA Rotary Tilt Buckets have a unique profile with a compact tip radius which enables the bucket to cut through the ground more effectively with minimal resistance and drag.

The self fill action gives an increased payload. These combined benefits result in time and fuel savings.

With no cylinders, pins, bushes or grease nipples and only two moving parts, the BTA range of tilt buckets offer superior advantages over cylinder style tilt buckets and are virtually maintenance free.

The BTA series is available for all machines from 1.5 to 70 tonnes.

The BTA range of buckets are manufactured from medium and high tensile steel which is wear resistant to optimise strength and weight. A wide selection of widths are available and wear strips are standard on all models above 5.5 tonne. A reversible bolt on cutting edge is optional. Custom built designs are also available on request.

Wear resistant leading edges

Optional bolt on Hardox cutting edge



Wear Strips

Up to 100°



Doherty Power Actuator

WWW.DOHERTYDIRECT.NET

The Doherty Power Actuator ensures precise control of the bucket with no unwanted movement.

The triple-sealed actuator is constantly lubricated with hydraulic oil, eliminating the need for daily greasing.

Because the hydraulic connections are stationary, the hose fit up is greatly simplified and the danger of hose damage is minimised.


The only regular maintenance is cleaning and lubricating the tertiary O ring end seals weekly which provides an additional level of sealing to ensure maximum service life.

Doherty Power Actuator at a Glance

- + Slim structure
- + Maintenance-free
- + Multiple connection ports
- + Specifically designed for excavator attachments
- + Triple sealed
- + Simple assembly
- + Only two moving parts
- + Integral relief valve
- + 100 degree tilt angle

End flange design provides huge bearing surface and special dust/dirt seals

The helix shaft and end flange is precision machined from a single billet then surface hardened



The housing and mounts are precision machined and treated with surface hardening and corrosion resistant process

The internal helix incorporates the piston and hydraulic seals

“
Using good quality, reliable equipment is important because you don't want any downtime.

I use Doherty buckets because the shape allows for easy filling and the Hardox steel keeps wear and tear to a minimum.”

Shane Brownell | Brownell Earthmoving

AUTHORISED DISTRIBUTOR



WWW.DOHERTYDIRECT.NET

Doherty Engineered Attachments Ltd

NZ +64 [0]7 574 3000 | **AUS** 1800 057 021 | **E** sales@dohertydirect.net

New Zealand

HEAD OFFICE - Postal: PO Box 9339, Greerton, Tauranga 3142, New Zealand. Physical: 98 Paerangi Place, Tauriko, Tauranga 3171, New Zealand

Australia

BRISBANE - Postal: PO Box 701, Annerley, QLD 4103, Australia. Physical: 2 / 2642 Ipswich Road, Darra, QLD, 4076, Australia

MELBOURNE - Factory 4, 21-22, National Drive, Hallam, VIC 3803, Australia

© Copyright Doherty Engineered Attachments Ltd, Doherty products are patent protected. All information contained herein is strictly confidential and intended for the individual or entity it is addressed/distributed to. Copies/unauthorised distribution is strictly prohibited. Doherty Engineered Attachments Ltd reserves the right to amend specifications/detail without prior notification.